

PoulChlor

Chlorinated Foam Cleaner

Product Code: I00733



CHLORINE

PoulChlor is suitable for use in food and beverage processing facilities, including federally inspected meat and poultry plants.

PoulChlor is a liquid formulation designed for use as a self-foaming, chlorinated cleaner for food processing facilities. It can be used on equipment in all departments when followed with a potable water rinse. PoulChlor contains detergents, chlorine, and alkaline caustic for an "all-in-one" action on hard to clean areas.

USAGE DIRECTIONS

Dilute 2 – 12 ounces of PoulChlor to each gallon of water as appropriate for the soil level. Apply foam, then rinse thoroughly with potable water.

SAFETY AND HAZARDS



Danger: Causes severe skin burns and eye damage. Do not breathe dusts or mists. Wash face, hands and any exposed skin thoroughly after handling.

Precautionary Statements: Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor.

IF SWALLOWED: Rinse mouth. Do not induce vomiting.

PRODUCT CLASS: Chlorine

Precautionary Statements: Storage

Store locked up.

Precautionary Statements: Disposal

Dispose of contents/container to an approved waste disposal plant.

Other Hazards

Toxic to aquatic life with long lasting effects.

PROTECTIVE EQUIPMENT

Precautionary Statements: Prevention

Wear protective gloves, protective clothing, eye protection, and face protection.



SAFETY GLOVES



PROTECTIVE CLOTHING



SAFETY GLASSES



FACE PROTECTION

PoulChlor

UN Number: UN1760
Product Code: I00733



DILUTION CHART AND TEST KIT

Application	Dilution Rate
Cleaning Applications	2.0 – 12.0 oz / gallon

Recommended Test Kit
TK-00014 Test Kit, Sodium Hydroxide

2 fl oz of product in 1 gallon is equivalent to 0.12% Sodium Hydroxide and 150 ppm of Chlorine.
Each drop (10 ml sample) is equivalent to 1.60 fl oz / gallon

TECHNICAL INFORMATION

Form..... Liquid
Color Clear-light
Odor Soapy
pH @ 1%..... 12.3
Foam High
Biodegradable Yes
Phosphates..... None
Density 1.069

ADDITIONAL WARNING

May damage painted surfaces, aluminum, brass, copper, galvanized and other soft metals.
Contains chlorine bleach. Do not mix with acids.

DOT SHIPPING NAME

UN1760, Corrosive liquids, n.o.s., (Potassium hydroxide, Sodium hydroxide, Sodium Hypochlorite), Hazard Class 8, PG II

Use these products with PoulChlor for a comprehensive sanitation program:

Birk-Ox
Foamacid
Liquik 20

Neutra Foam
Quadra-Quat
Ultra-Quat

MANUFACTURED BY



Birko Corporation
9152 Yosemite Street
Henderson, CO 80640
800.525.0476

www.birkocorp.com